

WAKOL D 3073 Universal Primer

Technical Information

Area of application

Ready-to-use dispersion-based universal primer for priming absorbent concrete and plastered surfaces, and for use as an adhesive bridge on non-absorbent subfloors indoors and outdoors.

Special properties

- solvent-free*
- suitable for chairs with castors
- very low emission**
- suitable over underfloor heating

* solvent-free according to the definition of the TRGS 610

** classified according to criteria of the GEV in Emission EC1: very low emission

Technical data

Raw material base:	polyacrylate dispersion
Cleaning agent:	water before adhesive dries
Method of application:	with velour or foam roller
Consumption:	approx. 100-150 g/m ²
Drying time:	when suitable for walking on subfloors not sensitive to moisture; at least 24 hrs. on moisture-sensitive subfloors.
Storage temperature:	not below +5°C, sensitive to frost
Storage time:	approx. 12 months at room temperature
Giscode:	D 1
Emission:	EC1

Subfloors:

The subfloor and the room climate conditions must satisfy the requirements of DIN 18356. Subfloors must be absorbent, level, permanently dry, firm and free of cracks, contamination and substances which hinder bonding.

Usage

Stir the pre-coat well before use. Apply WAKOL D 3073 with a foam roller on the subfloor. Avoid puddles. The levelling and bonding may be done after the primer is completely dry; observe drying times.

Important

Do not use below +15°C. Warm up the floor covering and adhesive in time in cold weather. WAKOL D 3073 do not use on magnesit screeds (stonewood screeds).

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

This Technical Information of 16.02.2010 supersedes all previous versions.