

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

1 Identification

- **Product identifier**
- **Trade name:** *WAKOL PS 205 Crack Filler B*
- **Application of the substance / the mixture** *Reaction resin*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Loba-Wakol, LLC
2732 Hwy 74 West
Wadesboro, NC 28170, USA
info@loba-wakol.com
+1 704 527 5919*
- **Information department:** *Product safety department.*
- **Emergency telephone number:**
*Emergency CONTACT (24-Hour-Number)
GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or
International (001) 352 323 3500*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** *Warning*

- **Hazard-determining components of labeling:**

ethane-1,2-diol

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- **Precautionary statements**

Avoid breathing mist/vapours/spray.

Wear protective gloves / eye protection.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 1)

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1344-09-8 Silicic acid, sodium salt >25–≤50%

⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319

107-21-1 ethane-1,2-diol >1–≤2.5%

⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373; ⚠ Acute Toxicity - Oral 4, H302

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Clean with water and soap. If possible, also wash with polyethylene glycol 400.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: **WAKOL PS 205 Crack Filler B**

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **PAC-1:**
1344-09-8 Silicic acid, sodium salt: 5.9 mg/m³
- **PAC-2:**
1344-09-8 Silicic acid, sodium salt: 65 mg/m³
- **PAC-3:**
1344-09-8 Silicic acid, sodium salt: 390 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only in well ventilated areas.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Protect from frost.
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

107-21-1 ethane-1,2-diol

TLV (USA)

Short-term value: 10** mg/m³, 50* ppm

Long-term value: 25* ppm

*vapor fraction: **inh. fraction, aerosol only, A4

WEEL (USA)

I (2)

IOELV (European Union) Short-term value: 104 mg/m³, 40 ppm

Long-term value: 52 mg/m³, 20 ppm

Skin

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not necessary if room is well-ventilated.

· **Protection of hands:**



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 4)

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-soluble (in water).

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1.48 g/cm³ (12.351 lbs/gal) (EN ISO 2811-1)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **Dynamic at 20 °C (68 °F):** 270 mPas (ISO 2555)

· **Kinematic:** Not determined.

· **VOC content:** 0.00 %

· **Solids content:** 52.0 % (DIN EN 827.8.2)

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 5)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Reacts with light alloys to form hydrogen.
Strong exothermic reaction with acids.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

1344-09-8 Silicic acid, sodium salt
Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
>5,000 mg/kg (rat)

107-21-1 ethane-1,2-diol
Oral LD50 14,600 mg/kg (mouse)
5,840 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rabbit)
9,530 mg/kg (rabbit)
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:**
Irritating effect.
Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.
- **NTP (National Toxicology Program)**

None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
 - 107-21-1 ethane-1,2-diol**
 - LC50/96h > 18,500 mg/l (piscarius)
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Void
- **UN proper shipping name**
- **DOT, ADR, ADN, IMDG, IATA** Void
- **Transport hazard class(es)**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Void
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:** Not dangerous according to the above specifications.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 7)

- **DOT**
- **Remarks:** not regulated

- **ADR**
- **Remarks:** not regulated

- **IMDG**
- **Remarks:** not regulated

- **IATA**
- **Remarks:** not regulated
- **UN "Model Regulation":** Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):**
All ingredients are listed or are not required to be listed on the TSCA inventory.
- **Hazardous Air Pollutants**
107-21-1 ethane-1,2-diol
- **Proposition 65**
- **Chemicals known to cause cancer:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.
- **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.
- **New Jersey Right-to-Know List:**
None of the ingredients is listed.
- **New Jersey Special Hazardous Substance List:**
None of the ingredients is listed.
- **Pennsylvania Right-to-Know List:**
None of the ingredients is listed.
- **Pennsylvania Special Hazardous Substance List:**
None of the ingredients is listed.
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 8)

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** *Warning*

· **Hazard-determining components of labeling:**

ethane-1,2-diol

· **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

· **Precautionary statements**

Avoid breathing mist/vapours/spray.

Wear protective gloves / eye protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

· **National regulations:**

· **VOC:**

· **VOC (EU)** 0.0 g/l

· **VOC (USA):** 0.0 g/l / 0.00 lb/gal

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Contact:**

· **Date of preparation / last revision** 10/24/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/24/2023

Reviewed on 10/24/2023

Trade name: WAKOL PS 205 Crack Filler B

(Contd. of page 9)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

US