

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

1 Identification

- **Product identifier**
- **Trade name:** *WAKOL PS 205 Crack Filler A*
- **Application of the substance / the mixture** *Reaction resin*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Loba-Wakol, LLC
2732 Hwy 74 West
Wadesboro, NC 28170, USA
info@loba-wakol.com
+1 704 527 5919
- **Information department:** *Product safety department.*
- **Emergency telephone number:**
Emergency CONTACT (24-Hour-Number)
GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or
International (001) 352 323 3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Sensitization - Respiratory 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomeres and homologues

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 1)

· Hazard statements

- Harmful if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- Suspected of causing cancer.
- May cause respiratory irritation.
- May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wear protective gloves/protective clothing/eye protection/face protection.
- [In case of inadequate ventilation] wear respiratory protection.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Call a poison center/doctor if you feel unwell.
- Specific treatment (see on this label).
- If experiencing respiratory symptoms: Call a poison center/doctor.
- Wash contaminated clothing before reuse.
- Store in a well-ventilated place. Keep container tightly closed.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues >50–≤100%
 ⚠ Sensitization - Respiratory 1, H334; Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; ⚠ Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335

US

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: **WAKOL PS 205 Crack Filler A**

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:** *Clean with water and soap. If possible, also wash with polyethylene glycol 400.*
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** *Do not induce vomiting; immediately call for medical help.*
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
· **Indication of any immediate medical attention and special treatment needed**
In cases of irritation to the lungs, initial treatment with Dexamethason metered aerosol.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
*Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.*
- **Additional information**
*Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
*Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.*
- **Environmental precautions:**
*Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 3)

- **PAC-1:**
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 0.15 mg/m³
- **PAC-2:**
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 3.6 mg/m³
- **PAC-3:**
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 22 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Prevent formation of aerosols.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Recommended filter device for short term use:** Combination filter A-P2
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 4)

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Color:

Brown

· **Odor:**

Weak, characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

10 °C (50 °F)
ca. 10 °C (ca. 50 °F)

Boiling point/Boiling range:

>260 °C (>500 °F)

· **Flash point:**

>200 °C (>392 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Auto igniting:**

>600 °C (>1,112 °F)
> 600 °C (> 1,112 °F)

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

· **Vapor pressure at 20 °C (68 °F):**

0.00001 hPa (0 mm Hg)
0.00001 hPas

· **Density at 20 °C (68 °F):**

1.13 g/cm³ (9.43 lbs/gal) (EN ISO 2811-1)

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 5)

- **Relative density** *Not determined.*
- **Vapor density** *Not determined.*
- **Evaporation rate** *Not determined.*
- **Solubility in / Miscibility with Water:** *Not miscible or difficult to mix.*
- **Partition coefficient (n-octanol/water):** *Not determined.*
- **Viscosity:**
 - Dynamic at 20 °C (68 °F):** *150 mPas (ISO 2555)*
 - Kinematic:** *Not determined.*
- **VOC content:** *0.00 %*
- **Other information** *No further relevant information available.*

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *Reacts with alcohols, amines, aqueous acids and alkalis.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral LD50 >10,000 mg/kg (rat) (OECD RL 401)

Dermal LD50 >9,400 mg/kg (rabbit) (OECD RL 402)
- **Primary irritant effect:**
 - **on the skin:** *Irritant to skin and mucous membranes.*
 - **on the eye:**
 - Irritating effect.*
 - Based on available data, the classification criteria are not met.*
- **Sensitization:**
 - Sensitization possible through inhalation.*
 - Sensitization possible through skin contact.*
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:*
 - Harmful*
 - Irritant*
 - When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.*

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 6)

- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 3
- **NTP (National Toxicology Program)**
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues
LC50/96h >1,000 mg/l (Danio rerio)
LC0/96h >1,000 mg/l (Brachydanio rerio)
EC50/24h >100 mg/l (bacteriums)
EC50/48h >1,000 mg/l (Daphnia magna)
EC50/3h >100 mg/l (sludge) (OECD 209)
- **Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Void

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: **WAKOL PS 205 Crack Filler A**

(Contd. of page 8)

· **New Jersey Special Hazardous Substance List:**

None of the ingredients is listed.

· **Pennsylvania Right-to-Know List:**

None of the ingredients is listed.

· **Pennsylvania Special Hazardous Substance List:**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomeres and homologues

· **Hazard statements**

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

· **National regulations:**

· **VOC:**

· **VOC (EU)** 0.0 g/l

· **VOC (USA):** 0.0 g/l / 0.00 lb/gal

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/26/2023

Reviewed on 10/26/2023

Trade name: WAKOL PS 205 Crack Filler A

(Contd. of page 9)

· Relevant phrases

- H315 Causes skin irritation.*
- H317 May cause an allergic skin reaction.*
- H319 Causes serious eye irritation.*
- H332 Harmful if inhaled.*
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H335 May cause respiratory irritation.*
- H351 Suspected of causing cancer.*
- H373 May cause damage to organs through prolonged or repeated exposure.*

· Contact:**· Date of preparation / last revision 10/26/2023****· Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- DOT: US Department of Transportation*
- IATA: International Air Transport Association*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- NFPA: National Fire Protection Association (USA)*
- HMIS: Hazardous Materials Identification System (USA)*
- VOC: Volatile Organic Compounds (USA, EU)*
- MAL-Code: Måleteknisk Arbejdshygiejnisk Lufibehov (Regulation for the labeling concerning inhalation hazards, Denmark)*
- LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- OSHA: Occupational Safety & Health*
- TLV: Threshold Limit Value*
- PEL: Permissible Exposure Limit*
- REL: Recommended Exposure Limit*
- Acute Toxicity - Inhalation 4: Acute toxicity – Category 4*
- Skin Irritation 2: Skin corrosion/irritation – Category 2*
- Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A*
- Sensitization - Respiratory 1: Respiratory sensitisation – Category 1*
- Sensitization - Skin 1: Skin sensitisation – Category 1*
- Carcinogenicity 2: Carcinogenicity – Category 2*
- Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*
- Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2*