

no stress whitening in combination

with Wakol MS-parquet adhesives

# WAKOL PK 4535 Colour paste, brown

# **Technical Information**

# Area of application

Brown colour paste to stain all kind of not dark coloured Wakol MS-parquet adhesives, Wakol polyurethane adhesives and Wakol dispersion adhesives.

•

#### **Special properties**

- solvent-free\*
- product features of the parquet adhesives stay preserved

\*solvent-free according to the definition of the TRGS 610

# **Technical data**

Raw material base:	pigment concentrate
Max. Dosage amount:	1 tube per packaging polyurethane parquet adhesive; 2 tubes per packaging Wakol MS parquet adhesive and Wakol dispersion adhesive
Storage time:	24 months at 20°C
GISCODE:	non-applicable

# Usage

Make a cut at the bottom of the inliner of Wakol MS-parquet adhesives and pour the adhesive into the bucket.

Add WAKOL PK 4535 Colour paste, brown to the corresponding adhesive. The addition can take place at the same time with the hardener of 2-K polyurethane adhesives.

Stir in intensely the WAKOL PK 4535 Colour paste, brown for at least 3 minutes and afterwards process the adhesive as usual.

Observe the Technical Information Sheet of the parquet flooring manufactures as well.

# Important

Lower addition amounts results in brighter brown tones. The adhesive can be individually adapt at the colour of the parquet, but do not exceed the maximum dosage.

The colour of the dispersion adhesive, after the stirring of the colour paste, is brighter in fresh condition. After the drying, the colour gets darker.

On top opened adhesive joints getting brighter after sanding. After using of finishing materials, adhesive gets darker again.

WAKOL PK 4535 Colour paste, brown is not suitable for dying synthetic resin solvents.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 02.07.2012 supersedes all previous versions.

O:\TI-GUELTIG\TI Bau\englisch\4535GB0102 0712 WAKOL PK 4535.doc Stand: 02.07.2012 Formular: F31TBGB, Revision: 4

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at Wakol Adhesa AG/SA Stauffacherstraße 130 A CH-3014 Bern Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl Via Kennedy 75 I-20010 Marcallo con Casone Tel, +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp. z o. o. ul. Sławęcinska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel. +48224362420 Fax +48224362421 www.loba-wakol.pl Maiburg Lijmen B.V. Schutweg 6 NL-5145 NP Waalwijk Tel. +31416566530 Fax +31416566531 www.maiburg.nl

page 2 of 2