The perfect hold with every application!





WAKOL D 3319 LVT Flooring Adhesive, contains fibre

Quick – bonds immediately Economical – very low consumption Firm – high fibre content prevents intentations on the surface







WAKOL D 3319 LVT Flooring Adhesive, contains fibre – powerful bond with maximum fibre reinforcement



Minimises floor movement during laying

WAKOL D 3319 LVT Flooring Adhesive, contains fibre holds flooring in place even while it is still wet, thus minimising the risk of floorplanks and tiles shifting during laying. This ensures that laying flooring using a wet adhesive layer is extremely straightforward and convenient.

Surfaces are safe to walk over in no time

The fibres in the adhesive form a structure that provides reinforcement even when wet, ensuring internal cohesion at an early stage. WAKOL D 3319 LVT Flooring Adhesive, contains fibre has a short setting time, meaning that the adhesive ridge quickly gains strength. The surface can be walked over – carefully – soon after the flooring has been laid.

High level of resistance against changes in flooring dimensions

The strong fibre reinforcement creates a high degree of resistance, counteracting undesired changes to dimensions in LVT flooring. This ensures that the chance of joint forming is kept to a minimum. It additionally minimises the risk of specks forming.

Provides protection against residual indentations

The fibres in WAKOL D 3319 LVT Flooring Adhesive, contains fibre counteract residual indentations. The fibre reinforcement prevents the adhesive layer being squeezed out of place. The high proportion of fibres also regulates the quantity of adhesive applied.



Highly cost-effective

Using the TKB A2 notched trowel, the amount of wet layer adhesive used is as little as 250-300 g/m². Despite these low quantities, the adhesive bond provided for LVT flooring far exceeds the requirements set out in the DIN EN 14259 standard.

Suitable for a wide range of applications

In addition to standard commercial LVT flooring in the form of planks and tiles, WAKOL D 3319 LVT Flooring Adhesive, contains fibre can also be used to install PVC and CV flooring in sheets and rolls.

Please always observe the technical information before processing.

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com

