

Version number 11 (replaces version 10) Revision: 13.01.2023 Printing date 13.01.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com +49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive
- · Dangerous components:

CAS: 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate >0.1-<0.25%

EINECS: 258-207-9 🚸 Repr. 2, H361f; 🥎 Eye Dam. 1, H318; 🕸 Aquatic Acute 1, Reg.nr.: 01-2119537297-32 H400; Aquatic Chronic 2, H411

· Additional information For the wording of the listed hazard phrases refer to section 16.



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

(Contd. of page 1)

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from humidity and water.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

GB



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

(Contd. of page 2)

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

#### 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

Oral DNEL 0.4 mg/kg/day (conmsumer (long-term))

Dermal DNEL 2.82 mg/kg/day (workers (short-term))

1.6 mg/kg/day (workwr (long-term))

Inhalative DNEL 0.8 mg/kg/day (conmsumer (long-term))

DNEL 0.69 mg/m³ (conmsumer (long-term))

· PNECs

### 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

PNEC 0.018 mg/l (freshwater)

0.0018 mg/l (sea water)

0.007 mg/l (water - partially release)

1 mg/l (STP)

PNEC 5.9 mg/kg (soil)

2.9 mg/kg (sediment (sea water))

29 mg/kg (sediment (freshwater))

· Additional information:

The lists valid during the making were used as basis.

See Section 10.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.35$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

(Contd. of page 3)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Smell:
Odour less
Odour threshold:
Melting point/freezing point:
Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined. · Flammability Not applicable.

· Lower and upper explosion limit

Lower:

Lower:

Not determined.

Vupper:

Not determined.

Flash point:

Decomposition temperature:

Not determined.

Not determined.

• **Decomposition temperature:**• **pH**• Not determined.

Not determined.

· Viscosity:

• Kinematic viscosity Not determined.

kinematic (calculated) at 40°C:

- dynamic at 20 °C: 170,000 mPas (ISO 2555)

Solubility

• Water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Steam pressure: Not determined.

· Density and/or relative density

• **Density at 20 °C** 1.83 g/cm³ (EN ISO 2811-1)

Relative density
Vapour density
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

Important information on protection of health and

environment, and on safety.

Self-inflammability:
Produc

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product does not present an explosion hazard.

• Organic solvents: 0.1 %
• VOC 0.1 %

• **Solids content:** 98.8 % (DIN EN 827.8.2)

(Contd. on page 5)



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

		(Contd. of page 4)
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical hazard classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammable		
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: Product releases low quantities of methanol during appropiated application.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

### 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

Oral LD50 3,700 mg/kg (rat)

Dermal LD50 3,170 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

(Contd. of page 5)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

## 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

NOEC/21d (static) 0.23 mg/l (Daphnia magna) (OECD RL 211)

LC50/96h 4.4 mg/l (Leuciscus macrochirus) (OECD RL 203) EC50/48h 8.6 mg/l (Daphnia magna) (OECD RL 202 T1)

EC50/3h >100 mg/l (sludge) (OECD RL 209)

EC50/72h 0.705 mg/l (Scenedesmus subspicatus) (RL 92/69/EWG, C.3) • 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 7)



Printing date 13.01.2023 Version number 11 (replaces version 10) Revision: 13.01.2023

Void

Trade name: WAKOL MS 265 Parquet Adhesive, firm-elastic

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class

· 14.4 Packing group

· ADR, IMDG, IATA Void

• 14.5 Environmental hazards: Not applicable. • 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

*instruments* Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· UN "Model Regulation": Void

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · VOC (EU) 1.3 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H318 Causes serious eye damage.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Repr. 2: Reproductive toxicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2