Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: WAKOL Applicator 50
- \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Lithium Ion Battery
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com +49 6331 8001 0
- Informing department: Product safety department. msds@wakol.de
- 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

U U

• 2.1 Classification of the substance or mixture This product is considered an article under the UK REACH Regulation.

- · Classification according to Regulation (EC) No 1272/2008
- The product is not classified, according to the GB CLP regulation.

· 2.2 Label elements

Within the meaning of the UK REACH-Regulation:

This mixture is not considered a hazard when used in a manner which is consistent with the labeled directions.

This mixture is considered an article in its final form.

This MSDS covers the hazards and information of the material contained within the article, in the event the product is damaged or mishandled.

Under normal conditions of use these chemicals are not anticipated to be available for exposure. Substances within this product may be reactive with water, air, and are flammable if released.

Thermal decomposition of this product may generate corrosive and toxic vapors.

In particular Hydrofluoric acid may be released in case of open cells.

Hydrofluoric acid can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive. See section 2.3 for hazards related to the ingredients encased within this product.

Avoid extremely high or low temperatures, keep away from incompatible materials.

Do not open, puncture, damage, or incinerate container.

Keep out of reach of children.

Store batteries in a dry and cool place!

- · Labelling according to Regulation (EC) No 1272/2008 Void
- Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

· 2.3 Other hazards

H301 - Toxic if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

Contains nickel monoxide, cobalt oxide. May produce an allergic reaction.

GB

Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

(Contd. of page 1)

GB

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

H410 - Very toxic to aquatic life with long lasting effects.

• Results of PBT and vPvB assessment

• *PBT*: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Jungerous components.	
CAS: 1313-13-9 manganese dioxide, ore of Chapter 26 EINECS: 215-202-6 STOT RE 2, H373; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332	10-<20%
CAS: 1313-99-1 nickel monoxide EINECS: 215-215-7 🚸 Carc. 1A, H350i; STOT RE 1, H372; 아 Skin Sens. 1, H317; Aquatic Chronic 4, H413	10-<20%
CAS: 1307-96-6 cobalt oxide EINECS: 215-154-6	10-<20%
CAS: 21324-40-3 Lithiumhexafluorophosphat EINECS: 244-334-7 🚸 Acute Tox. 3, H301; 🚸 STOT RE 1, H372; 🕎 Skin Corr. 1A, H314; Eye Dam. 1, H318	5%
CAS: 7440-50-8 copper EINECS: 231-159-6 🕸 Aquatic Chronic 2, H411	2.5-<10%
CAS: 7429-90-5 aluminium EINECS: 231-072-3 substance with a Community workplace exposure limit	2.5-<10%
\cdot Additional information For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures
General information
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation
Exposure to the contents of an open or damaged battery:
Supply fresh air; consult doctor in case of complaints.
After skin contact
Exposure to the contents of an open or damaged battery:
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
(Contd. on page 3)



Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

(Contd. of page 2)

- · After eye contact
- *Exposure to the contents of an open or damaged battery:*
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing

Exposure to the contents of an open or damaged battery:

Rinse out mouth. Call a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- + 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, sand, extinguishing powder. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources.
 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Keep receptacles tightly sealed. • Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB



Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Components with critical values that require monitoring at the workplace:

1313-13-9 manganese dioxide, ore of Chapter 26

WEL Long-term value: 0.2* 0.05** mg/m³ as Mn *inhalable fraction **respirable fraction

1313-99-1 nickel monoxide

WEL Long-term value: 0.5 mg/m³ as Ni; Sk; Carc

1307-96-6 cobalt oxide

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

7440-50-8 copper

WEL Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume **dusts and mists (as Cu)

7429-90-5 aluminium

WEL Long-term value: 10* 4** mg/m³ *inhalable dust ** respirable dust

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands before breaks and at the end of work.
- Breathing equipment:

Not required under normal conditions of use.

When handling damaged batteries:

Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exeed established Occupational Exposure Limits.

• Hand protection

Not required under normal conditions of use. When handling damaged batteries:

Wear chemically resistant protective gloves.

• Eye/face protection

Not required under normal conditions of use. When handling damaged batteries:

Chemical goggles or safety glasses.

(Contd. on page 5)

GR



Printing date 06.07.2022

Anspruch verbindet

/dko

Version number 10 (replaces version 1)

Revision: 06.07.2022

(Contd. of page 4)

Trade name: WAKOL Applicator 50

· Body protection:

Not required under normal conditions of use. When handling damaged batteries: Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

General Information Colour:	According to product specification	
Smell:	Odourless	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and boiling	chaeler minea.	
range	Undetermined.	
Flammability	Contact with water liberates extremely flammable gases.	
Lower and upper explosion limit	Contact with water tiber ales extremely funituate gases	
Lower:	Not determined.	
Upper:	Not determined.	
Flash point:	Not applicable.	
Decomposition temperature:	Not determined.	
pH	Not applicable.	
Viscosity:		
riscosity. Kinematic viscosity	Not applicable.	
kinematic (calculated) at 40°C:		
dynamic:	Not applicable.	
<i>solubility</i>	Not applicable.	
Water:	Insoluble.	
Organic solvents:	well soluble	
Partition coefficient n-octanol/water (log value)	Not determined.	
	Not applicable.	
Steam pressure: Density and/or volating density	Noi applicable.	
Density and/or relative density	Not determined.	
Density Belative density	Not determined.	
Relative density		
Vapour density	Not applicable.	
9.2 Other information		
Appearance:		
Form:	Solid	
Important information on protection of health and	d	
environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Change in condition	-	
Evaporation rate	Not applicable.	
Information with regard to physical hazard classe	\$	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
P	(Contd. on page	

Printing date 06.07.2022

Anspruch verb

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

		(Contd. of page 5)
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

+11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	ion
· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN3481
14.2 UN proper shipping name	
ADR	Void
· IMDG, IATA	LITHIUM ION BATTERIES PACKED WITH Equipment
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
EMS Number:	F-A,S-I
Stowage Category	A
	(Contd. on page 8





Printing date 06.07.2022

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

· Stowage Code	(Contd. of page 7) SW19 For batteries transported in accordance with SP 376 or SP 377 Category C, unless transported on a short international voyage.	
• 14.7 Maritime transport in bulk accordin	ng to IMO	
instruments	Not applicable.	
• Transport/Additional information:		
ADR	Transportation according to special provision 188	
Limited quantities (LQ)	0	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	E	
· IMDG	Transportation according to special provision 188	
IATA	Transportation according to special provision 188	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- **VOC (EU)** 0.0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H350i May cause cancer by inhalation.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)

GB





Printing date 06.07.2022

Anspruch verbindet

Version number 10 (replaces version 1)

Revision: 06.07.2022

Trade name: WAKOL Applicator 50

(Contd. of page 8) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1A: Carcinogenicity - Category 1Ai Carc. 2: Carcinogenicity - Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4