

WAKOL L 1806 Adhesion Promoter

Technical Information

Area of application

Primer for increasing the adhesion of WAKOL MS 425 Decking Sealant, black when grouting ship decks in the indoor and outdoor area.

Technical data

Raw material base:	organic solvent mixture
Application method:	brush
Drying time:	min. 30 minutes, max. 4 hours
Storage temperature:	store in a cool location not sensitive to frost
Temperature during use:	not below +5 °C
Storage time:	9 months at room temperature

Subfloors

Replace defective timbers and sand the joint edges during renovations.
Only use WAKOL L 1806 Adhesion Promoter on absorbent subfloors.
The joints must be clean, dry and free of grease and old sealants.

Usage

Using a brush apply a thin layer of WAKOL L 1806 Adhesion Promoter on the joint edges. WAKOL L 1806 Adhesion Promoter leaves a more or less visible residue. Therefore, wipe off any spilt or undesired adhesion promoter immediately. After the adhesion promoter has dried, it can generally only be removed again by mechanical means, e.g. sanding. It is therefore strongly recommended to mask the areas around the joint. In the case of teak decking, which is sanded after grouting, masking the adjacent surface is not necessary.

The drying time is at least 30 minutes at +20 °C. At the latest 4 hours after the adhesion promoter has been applied the joint must be grouted with WAKOL MS 425 Decking Sealant, black. If the time frame has lapsed, the surface of the joint edges must be checked again for cleanliness. The drying time is at least 30 minutes at +20 °C. At the latest 4 hours after the adhesion promoter has been applied the joint must be grouted with WAKOL MS 425 Decking

Sealant, black. If the time frame has lapsed, the surface of the joint edges must be checked again for cleanliness.

Important

WAKOL L 1806 Adhesion Promoter cannot be processed at temperatures below +5 °C or above +30 °C.

The solvent must have evaporated before the sealant or adhesive is applied. The stated drying times must be observed.

The product must be used within 2 months of opening the container.

All information is based on approx. 20 °C and 50 % relative air humidity.

Warm up all laying materials in due time in heated room.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 05.04.2023 supersedes all previous versions.