

WAKOL RS 5945 Edging Strips

Technical Information

Area of application

Permanently elastic edge strips made from polyethylene with a self-adhesive base to be used before applying levelling compound in thicker layers and before applying WAKOL Z 515 Thin Screed.

Technical data

Material:	5 mm thick and 50 mm high self-adhesive PE insulation strips
Delivery:	Rolls, each 25 m 4 rolls per box
Storage time:	12 months at room temperature
Storage temperature:	store in a cool location not sensitive to frost

Usage

Remove the protective cover and bond the self-adhesive base directly to the dust-free subsurface that you are renovating; the angle strain presses the insulation strips to the wall. The levelling compound can be directly applied to the matted backing on the base.

Important (Notes)

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 11.08.2022 supersedes all previous versions.

Wakol GmbH
Bottenbacher Straße 30
D-66954
Pirmasens
Tel. +49 6331 8001 131
Fax +49 6331 8001 890
www.wakol.com



Wakol GmbH
Industriestraße 5
A-6841
Mäder
Tel. +43 5523 64 700
Fax +43 5523 64 700 64
www.wakol.at

Wakol Adhesa AG
Schützengasse 28
CH-9410
Heiden
Tel. +41 31 9210 755
Fax +41 31 9212 968
www.wakoladhesa.ch

Wakol Foreco srl
A Via Kennedy 75
I-20010
Marcallo con Casone
Tel. +39 02 9761 939
Fax +39 02 97 253 021
www.wakolforeco.it

Loba-Wakol Polska Sp.z o.o.
ul. Sławęcińska 16, Macierzysz
PL-05-850
Ożarów Mazowiecki
Tel. +48 22 436 24 20
Fax +48 22 436 24 21
www.loba-wakol.pl

Lecol Chemie B.V.
Schutweg 6
NL-5145 NP
Waalwijk
Tel. +31 416 566 540
Fax +31 416 566 531
www.lecol.nl