

Strike with no effort at all!



WAKOL MS 292 Wood Flooring Adhesive

New – first shear-resistant MS Wood Flooring adhesive in tubular bag

Modern – optimized for ergonomic and efficient use with WAKOL Applicator 90

Tried & Tested – best-in-class WAKOL MS Technology

Safe – no interaction with finishes and VOC free!

Product:



WAKOL® 
Anspruch verbindet



WAKOL MS 292 Wood Flooring Adhesive – fast, clean and comfortable usage



Shear-resistant MS Wood Flooring adhesive for all types of parquet and wood

WAKOL MS 292 Wood Flooring Adhesive is a shear-resistant MS polymer adhesive which reliably bonds critical wood types and parquet dimensions. It complies with the requirements of DIN EN 14293 and ISO 17178 for the group of "hard parquet adhesives".

With its exceptionally high suction adhesion, WAKOL MS 292 Wood Flooring Adhesive holds even long parquet boards securely to the floor when installing.

Comfortable squeeze with zero drip!

WAKOL MS 292 Wood Flooring Adhesive was specifically developed for use in adhesive applicators with a minimum diameter of 90 mm, such as the WAKOL Applicator 90.

Zero VOC & No interaction with finish

WAKOL MS 292 Wood Flooring Adhesive has no VOC content or any plasticising substances. Ruling out the migration of adhesive components that interact with wood finishes.

Connected systems – the perfect match

WAKOL MS 292 Wood Flooring Adhesive, is part of the Loba and Wakol "Connected System" guarantee. This means that WAKOL MS 292 Wood Flooring Adhesive and recommended Loba coatings are compatible. No more worries about unwanted interactions between the products – we guarantee it!

Efficient

The applicator method consistently produces lower consumption in comparison to a trowel application. The amount of adhesive can be adapted to the Wood Flooring width by simply changing to a different size WAKOL Replaceable Nozzle.



WAKOL PU 280 Moisture Barrier or WAKOL MS 325 Moisture Barrier can be used for waterproofing and priming of porous and non-porous subfloors prior to the installation of WAKOL MS 292 Wood Flooring Adhesive.

Less waste

When used in an applicator, foil tubes make it easy to ensure that you utilize every last drop. This eliminates the tiresome, time-consuming task of scraping traces of adhesive from the bottom of your pail. When crushed, the foil tubes occupy significantly less landfill space than bulky stacks of adhesive containers.

The closed system foil tubes protect remaining adhesive from moisture in the air in the building when you are working. Even when the packaging is opened, the surface of the product does not start to dry out or form a skin. This ensures that the adhesive you apply will always be fresh.

For all other information, please always refer to the Product Data Sheet.



Loba-Wakol LLC
2401 Whitehall Park Drive - Suite 950
Charlotte, NC 28273, USA
Tel. +1 704 527 5919
Fax +1 704 527 5922
www.loba-wakol.com

WAKOL®
Anspruch verbindet